

Stainless steel wire rope, Ø 5 mm, 15 m kit



Use:

- Used by the sea or outdoors with specific customary requirements.

Technical properties

- Metallic central core - Right hand lay.
- Wire rope kit with sleeved thimble loop and stainless steel single eye hook.

Technical characteristics of Stainless steel wire rope, Ø 5 mm, 15 m kit

References	CB5KIT15MINOX
Mini. breaking load kg	1300
Theoretical weight kg/m	0,095
Pulling working load kg	433
Lifting working load wire rope kg	260
Construction	7 x 19
Wire rope Ø mm	5

Technical characteristics of the other models of the range

References	CB3KIT10MINOX	CB4KIT10MINOX	CB4KIT15MINOX	CB5KIT10MINOX	CB5KIT15MINOX
Mini. breaking load kg	460	830	830	1300	1300
Theoretical weight kg/m	0,034	0,061	0,061	0,095	0,095
Pulling working load kg	153	277	277	433	433
Lifting working load wire rope kg	92	166	166	260	260
Construction	7 x 19	7 x 19	7 x 19	7 x 19	7 x 19
Wire rope Ø mm	3	4	4	5	5

References	CB6KIT10MINOX	CB7KIT15MINOX	CB8KIT15MINOX
Mini. breaking load kg	1880	2560	3330
Theoretical weight kg/m	0,138	0,187	0,243
Pulling working load kg	627	853	1110
Lifting working load wire rope kg	376	512	666
Construction	7 x 19	7 x 19	7 x 19
Wire rope Ø mm	6	7	8



HUCHEZ
4, rue Michel HAMMID
60420 FERRIERES – France
☎ +33 (0) 3 44 51 11 33
🌐 www.huchez.com
✉ contact@huchez.fr



SERVICE CLIENTS
ATENCIO AL CLIENTE
KUNDENSERVICE

Pour en savoir plus, n'hésitez pas à nous contacter!
To know more, please contact us!
Para más información, póngase en contacto con nosotros!
Für weitere Informationen können Sie sich gerne an uns wenden!