

Galvanised non rotating wire rope with metallic central core 2170 N/mm², right

it



Use:

- Lifting non guided loads.

Technical properties

- Metallic central core 2170 N/mm² - Right hand lay.
- High breakage load.
- Great flexibility.
- Wire rope kit with sleeved thimble loop and single swivel hook.

Technical characteristics of Galvanised non rotating wire rope with metallic central core 2170 N/mm², right hand lay, Ø 9 mm, 40 m kit

References	CB9KIT40M
Mini. breaking load kg	6600
Theoretical weight kg/m	0,328
Pulling working load kg	2200
Lifting working load wire rope kg	1320
Construction	18 x 7
Wire rope Ø mm	9

Technical characteristics of the other models of the range

References	CB3KIT5M	CB3KIT10M	CB4KIT10M	CB4KIT15M	CB5KIT10M
Mini. breaking load kg	800	800	1100	1100	2300
Theoretical weight kg/m	0,037	0,037	0,083	0,083	0,111
Pulling working load kg	267	267	367	367	767
Lifting working load wire rope kg	160	160	220	220	460
Construction	18 x 7	18 x 7	18 x 7	18 x 7	18 x 7
Wire rope Ø mm	3	3	4	4	5

References	CB5KIT15M	CB5KIT20M	CB5KIT35M	CB5KIT50M	CB6KIT5M
Mini. breaking load kg	2300	2300	2300	2300	3050
Theoretical weight kg/m	0,111	0,111	0,111	0,111	0,150
Pulling working load kg	767	767	767	767	1017
Lifting working load wire rope kg	460	460	460	460	610
Construction	18 x 7	18 x 7	18 x 7	18 x 7	18 x 7
Wire rope Ø mm	5	5	5	5	6

References	CB6KIT10M	CB6KIT15M	CB7KIT15M	CB7KIT38M	CB8KIT15M
Mini. breaking load kg	3050	3050	3750	3750	5600
Theoretical weight kg/m	0,150	0,150	0,185	0,185	0,290
Pulling working load kg	1017	1017	1250	1250	1867
Lifting working load wire rope kg	610	610	750	750	1120
Construction	18 x 7	18 x 7	18 x 7	18 x 7	18 x 7
Wire rope Ø mm	6	6	7	7	8

References	CB8KIT35M	CB8KIT50M	CB9KIT15M	CB9KIT40M	CB115KIT45M
Mini. breaking load kg	5600	5600	6600	6600	11000
Theoretical weight kg/m	0,290	0,290	0,328	0,328	0,588
Pulling working load kg	1867	1867	2200	2200	3667
Lifting working load wire rope kg	1120	1120	1320	1320	2200
Construction	18 x 7	18 x 7	18 x 7	18 x 7	18 x 7
Wire rope Ø mm	8	8	9	9	11,5



HUCHEZ
4, rue Michel HAMMID
60420 FERRIERES – France
☎ +33 (0) 3 44 51 11 33
🌐 www.huchez.com
✉ contact@huchez.fr



SERVICE CLIENTS
ATENCIO AL CLIENTE
KUNDENSERVICE

Pour en savoir plus, n'hésitez pas à nous contacter!
To know more, please contact us!
Para más información, póngase en contacto con nosotros!
Für weitere Informationen können Sie sich gerne an uns wenden!