TIREX 300 kg - stainless steel model





Hand spurgear winch 300 kg, stainless steel model (with stainless steel mounting plate).
Use:
- Lifting or pulling/hauling operations
- Indoor - Outdoor
- Operating temperature between -10°C and +50°C
- Flat position
- Lifting doors
- Opening of traps
- On trailers, masts...

Comply with Machines Directive 2006/42/EC. Developped and manufactured in accordance with standard NF E N 13157.

Technical properties


- A new generation, compact winch taking advantage of the qualities of composite materials and aluminium, especially their anti-corrosion properties.
- High force/compact and density ratio.
- Many possibilities of wire rope exit (over 250°).
- Ergonomically and comfortably shaped crank grip.
- Removable crank.
- Stainless steel spring and pawls.
- Automatic brake.
- Stainless steel mounting plate.
- Disengageable drum, no load only, associated with a failsafe system in the rope wind direction (patented).
- Planetary reducer in a sealed casing.
- Gear system with satellite pinions offering excellent mechanical balance and reducing the effort required on the crank.

Technical characteristics of TIREX 300 kg - stainless steel model

Capacity 1st layer kg	400
Capacity top layer kg	300
Nb of layers	3
Wire rope cap. 1st layer m	2
Max. rope capacity m	8,5
Wire rope Ø mm	5
Weight (without wire rope) kg	3,7
Lift per crank revolution mm	41
Max. hand force on crank kg	14

Dimensions

A mm	61
B mm	100
C mm	320
D mm	189
E mm	144
F mm	250
G mm	126
H mm	60
I mm	11



Technical characteristics of the other models of the range

References	TIREX150	TIREX150INOX	TIREX300	**TIREX300INOX**
Capacity 1st layer kg	250	250	400	**400**
Capacity top layer kg	150	150	300	**300**
Nb of layers	6	6	3	**3**
Wire rope cap. 1st layer m	2,5	2,5	2	**2**
Max. rope capacity m	24	24	8,5	**8,5**
Wire rope Ø mm	4	4	5	**5**
Weight (without wire rope) kg	3,7	3,7	3,7	**3,7**
Lift per crank revolution mm	40	40	41	**41**
Max. hand force on crank kg	8	8	14	**14**



HUCHEZ's advice

High force/compact and density ratio, many possibilities of wire rope exit (over 250°), clutch release impossible when loaded, accessible and very safe self-tightening rope attachment, rope guide for correct winding and a maximum safety with two ratchets.

HUCHEZ
4, rue Michel HAMMID
60420 FERRIERES – France
+33 (0) 3 44 51 11 33
www.huchez.com
contact@huchez.fr

SERVICE CLIENTS
ATENCIO AL CLIENTE
KUNDENSERVICE

Pour en savoir plus, n'hésitez pas à nous contacter!
To know more, please contact us!
Para más información, póngase en contacto con nosotros!
Für weitere Informationen können Sie sich gerne an uns wenden!