
MANIBOX GR 300 kg - model with stainless steel frame







Hand spurgear winch 750 kg, model with stainless steel frame.
Use:
- Lifting or pulling/hauling operation
- Wall-mounted or flat
- Industry
- Auditoriums, theatre scenery
- Water treatment, water dams
- Sports rooms
- Hanging chandeliers...

Comply with Machines Directive 2006/42/EC. Developped and manufactured in accordance with standard NF E N 13157.

Technical properties


- Mechanical parts machined and protected by cataphoresis.
- Stainless steel ratchet spring.
- Straight-cut gears.
- Automatic brake made of composite materials.
- Disengageable drum, no load only, associated with a failsafe system in the rope wind direction (patented).
- Reduction system fully protected by a metal or plastic cover providing maximum safety.
- Ergonomic and removable crank handle with rotating grip, positioned on the left hand side. This crank arm can be adjusted to minimise effort according to the loads.
- Captive crank adjusting knob.
- Finition: stainless steel frame.

Technical characteristics of MANIBOX GR 300 kg - model with stainless steel frame

Capacity 1st layer kg	500
Capacity top layer kg	300
Nb of layers	6
Wire rope cap. 1st layer m	4
Max. rope capacity m	38
Wire rope Ø mm	5
Weight (without wire rope) kg	15
Lift per crank revolution mm	30.5
Max. hand force on crank kg	12.5

Dimensions

A mm	249
B mm	400
C mm	190
D mm	217
E mm	240
F mm	200
G mm	145
K mm	144
S mm	184
T mm	76



Technical characteristics of the other models of the range

References	**GR300INOX**	GR530PREMINOX	GR500INOX	GR750PREMINOX	GR1000INOX
Capacity 1st layer kg	**500**	530	750	750	1450
Capacity top layer kg	**300**	530	500	750	1000
Nb of layers	**6**	1	4	1	4
Wire rope cap. 1st layer m	**4**	4	3	3	5.5
Max. rope capacity m	**38**	4	18	3	30
Wire rope Ø mm	**5**	6	7	7	9
Weight (without wire rope) kg	**15**	15	15	15	44
Lift per crank revolution mm	**30.5**	30.5	31.5	31.5	16
Max. hand force on crank kg	**12.5**	12.5	19	19	14.5

References	GR1450PREMINOX	GR2000INOX	GR2750PREMINOX
Capacity 1st layer kg	1450	2750	2750
Capacity top layer kg	1450	2000	2570
Nb of layers	1	3	1
Wire rope cap. 1st layer m	5	6	6
Max. rope capacity m	5	25	6
Wire rope Ø mm	10	13	13
Weight (without wire rope) kg	44	83	83
Lift per crank revolution mm	16	9.5	9.5
Max. hand force on crank kg	14.5	16.5	16.5



HUCHEZ's advice

Captive crank adjusting knob, adjustable crank handle for fast winding or otherwise, maximum capacity, release does not operate under load, highly reliable rope fastener not requiring any special tools.

HUCHEZ
4, rue Michel HAMMID
60420 FERRIERES – France
+33 (0) 3 44 51 11 33
www.huchez.com
contact@huchez.fr

SERVICE CLIENTS
ATENCIO AL CLIENTE
KUNDENSERVICE

Pour en savoir plus, n'hésitez pas à nous contacter!
To know more, please contact us!
Para más información, póngase en contacto con nosotros!
Für weitere Informationen können Sie sich gerne an uns wenden!