MANIBOX VS 2000 kg, 5.5 m of rope - model with stainless steel frame







Hand wormgear winch 2000 kg, model with stainless steel frame.
Use:
- Lifting or pulling/hauling operation
- Wall-mounted or flat
- Industry
- Shows, sceneries
- Water treatment, water dams
- Sports rooms
- Hanging chandeliers...

Comply with Machines Directive 2006/42/EC. Developped and manufactured in accordance with standard NF E N 13157.

Technical properties


- Mechanical parts machined and protected by cataphoresis.
- Stainless steel ratchet spring.
- Absolute safety by worm screw and automatic brake.
- Reduction system fully protected by a metal or plastic cover providing maximum safety.
- Desengageable drum, no load only.
- Failsafe system in the rope wind direction (patented).
- Adjustable crank handle for fast winding or otherwise maximum capacity.
- Crank positioned on the right.
- Captive crank adjusting knob.
- Finition: stainless steel frame.

Technical characteristics of MANIBOX VS 2000 kg, 5.5 m of rope - model with stainless steel frame

Capacity 1st layer kg	2000
Capacity top layer kg	2000
Nb of layers	1
Wire rope cap. 1st layer m	5.5
Max. rope capacity m	6
Wire rope Ø mm	12
Weight (without wire rope) kg	52
Lift per crank revolution mm	6
Max. hand force on crank kg	14

Dimensions

A mm	350
B mm	518
D mm	330
E mm	370
F mm	200
G mm	-
K mm	250
L mm	340



Technical characteristics of the other models of the range

References	VS250INOX	VS320PREMINOX	VS500INOX	VS750PREMINOX	VS1000INOX
Capacity 1st layer kg	380	380	750	750	1450
Capacity top layer kg	250	320	500	750	1000
Nb of layers	4	2	4	1	4
Wire rope cap. 1st layer m	2.5	2.5	3	3	5.5
Max. rope capacity m	15	6	18	3	30
Wire rope Ø mm	5	6	7	7	9
Weight (without wire rope) kg	7.5	7.5	12	12	37.5
Lift per crank revolution mm	17	17	11	11	8
Max. hand force on crank kg	11	11	14	14	14

References	VS1450PREMINOX	VS1500INOX	**VS2000PREMINOX**	VS2000INOX	VS2500PREMINOX
Capacity 1st layer kg	1450		**2000**		2500
Capacity top layer kg	1450		**2000**		2500
Nb of layers	1		**1**		1
Wire rope cap. 1st layer m	5		**5.5**		7
Max. rope capacity m	5		**6**		6
Wire rope Ø mm	10		**12**		13
Weight (without wire rope) kg	37.5		**52**		80
Lift per crank revolution mm	8		**6**		5
Max. hand force on crank kg	14		**14**		14.5

References	VS3000INOX	VS3500PREMINOX
Capacity 1st layer kg	3500	3500
Capacity top layer kg	3000	3500
Nb of layers	2	1
Wire rope cap. 1st layer m	7.5	7.5
Max. rope capacity m	18.5	7.5
Wire rope Ø mm	16	16
Weight (without wire rope) kg	140	140
Lift per crank revolution mm	3	3
Max. hand force on crank kg	15	15



HUCHEZ's advice

Captive crank adjusting knob, adjustable crank handle for fast winding or otherwise, maximum capacity, highly reliable rope fastener not requiring any special tools, fail safe system in the rope wind direction.

HUCHEZ
4, rue Michel HAMMID
60420 FERRIERES – France
+33 (0) 3 44 51 11 33
www.huchez.com
contact@huchez.fr

SERVICE CLIENTS
ATENCIO AL CLIENTE
KUNDENSERVICE

Pour en savoir plus, n'hésitez pas à nous contacter!
To know more, please contact us!
Para más información, póngase en contacto con nosotros!
Für weitere Informationen können Sie sich gerne an uns wenden!