
4AFLM 80 kg - standard model







Hand self-braked spurgear winch 80 kg, standard model (zinc protection).
Use:
- Lifting or pulling/hauling operations
- Occasional use or leisure
- Small lifting height
- Hanging chandeliers
- Light trailer (quad, lawn tractor...)

Comply with Machines Directive 2006/42/EC. Developped and manufactured in accordance with standard NF E N 13157.

Technical properties


- Compact winch.
- Small size.
- Robust: chassis and steel drum.
- Automatic brake.
- Easy to install (2 points of fixation).
- To use with steel ropes.
- Stainless steel model available.

Technical characteristics of 4AFLM 80 kg - standard model

Capacity 1st layer kg	190
Capacity top layer kg	80
Max. rope capacity m	8
Wire rope Ø mm	3
Weight (without wire rope) kg	2.2

Dimensions

U mm	126
V mm	27
W mm	31
J mm	96
K mm	50
L mm	211
M mm	125
N mm	195
S mm	78
T mm	32



Technical characteristics of the other models of the range

References	**4AFLM**	4AFL	6AFL	8AFL	12AFL
Capacity 1st layer kg	**190**	340	500	650	900
Capacity top layer kg	**80**	190	240	270	490
Max. rope capacity m	**8**	10	12	19	12
Wire rope Ø mm	**3**	4	5	6	7
Weight (without wire rope) kg	**2.2**	2.5	3.6	5.5	7.4

References	4AFLMINOX	4AFLINOX	6AFLINOX	8AFLINOX	12AFLINOX
Capacity 1st layer kg	190	340	500	650	900
Capacity top layer kg	80	190	240	270	490
Max. rope capacity m	8	10	12	19	12
Wire rope Ø mm	3	4	5	6	7
Weight (without wire rope) kg	2	2.5	3.6	5.5	7.4



HUCHEZ's advice

Compact, easy to install and use.

HUCHEZ
4, rue Michel HAMMID
60420 FERRIERES – France
+33 (0) 3 44 51 11 33
www.huchez.com
contact@huchez.fr

SERVICE CLIENTS
ATENCIO AL CLIENTE
KUNDENSERVICE

Pour en savoir plus, n'hésitez pas à nous contacter!
To know more, please contact us!
Para más información, póngase en contacto con nosotros!
Für weitere Informationen können Sie sich gerne an uns wenden!