
6AFLX 240 kg - stainless steel model







Hand self-braked spurgear winch 240 kg, stainless steel model.
Use:
- Lifting or pulling/hauling operations
- Occasional use or leisure
- Small lifting height
- Hanging chandeliers
- Light trailer (quad, lawn tractor...)

Comply with Machines Directive 2006/42/EC. Developped and manufactured in accordance with standard NF E N 13157.

Technical properties


- Compact winch.
- Small size.
- Robust: chassis and steel drum.
- Automatic brake.
- Easy to install (2 or 3 points of fixation depending on models).
- To use with steel ropes.
- Stainless steel model available.

Technical characteristics of 6AFLX 240 kg - stainless steel model

Capacity 1st layer kg	500
Capacity top layer kg	240
Max. rope capacity m	12
Wire rope Ø mm	5
Weight (without wire rope) kg	3.6

Dimensions

U mm	161
V mm	27
W mm	58
J mm	128
K mm	99.5
L mm	265
M mm	155
N mm	240
S mm	132
T mm	32



Technical characteristics of the other models of the range

References	4AFLM	4AFL	6AFL	8AFL	12AFL
Capacity 1st layer kg	190	340	500	650	900
Capacity top layer kg	80	190	240	270	490
Max. rope capacity m	8	10	12	19	12
Wire rope Ø mm	3	4	5	6	7
Weight (without wire rope) kg	2.2	2.5	3.6	5.5	7.4

References	4AFLMINOX	4AFLINOX	**6AFLINOX**	8AFLINOX	12AFLINOX
Capacity 1st layer kg	190	340	**500**	650	900
Capacity top layer kg	80	190	**240**	270	490
Max. rope capacity m	8	10	**12**	19	12
Wire rope Ø mm	3	4	**5**	6	7
Weight (without wire rope) kg	2	2.5	**3.6**	5.5	7.4



HUCHEZ's advice

Compact, easy to install and use.

HUCHEZ
4, rue Michel HAMMID
60420 FERRIERES – France
+33 (0) 3 44 51 11 33
www.huchez.com
contact@huchez.fr

SERVICE CLIENTS
ATENCIO AL CLIENTE
KUNDENSERVICE

Pour en savoir plus, n'hésitez pas à nous contacter!
To know more, please contact us!
Para más información, póngase en contacto con nosotros!
Für weitere Informationen können Sie sich gerne an uns wenden!