

Standard wire rope galvanised, Ø 3 mm, m/l



Use:

- Used for lifting or pulling loads, but the load must be guided.

Technical properties

- Metallic central core 1960 N/mm² - Right hand lay.
- Available option: sleeved thimble loop.
- Single eye hook recommended.

Technical characteristics of Standard wire rope galvanised, Ø 3 mm, m/l

| References | CB3STG |
|-----------------------------------|--------|
| Mini. breaking load kg | 645 |
| Theoretical weight kg/m | 0,034 |
| Pulling working load kg | 215 |
| Lifting working load wire rope kg | 129 |
| Construction | 6 x 7 |
| Wire rope Ø mm | 3 |

Technical characteristics of the other models of the range

| References | CB3STG | CB4STG | CB5STG | CB6STG | CB7STG |
|-----------------------------------|--------|--------|--------|--------|--------|
| Mini. breaking load kg | 645 | 1152 | 1795 | 2560 | 3488 |
| Theoretical weight kg/m | 0,034 | 0,061 | 0,096 | 0,144 | 0,188 |
| Pulling working load kg | 215 | 384 | 598 | 853 | 1163 |
| Lifting working load wire rope kg | 129 | 230 | 359 | 512 | 698 |
| Construction | 6 x 7 | 6 x 7 | 6 x 7 | 6 x 19 | 6 x 19 |
| Wire rope Ø mm | 3 | 4 | 5 | 6 | 7 |

| References | CB8STG | CB9STG | CB10STG | CB12STG | CB13STG |
|-----------------------------------|--------|--------|---------|---------|---------|
| Mini. breaking load kg | 4559 | 5763 | 7119 | 10200 | 12036 |
| Theoretical weight kg/m | 0,246 | 0,311 | 0,384 | 0,553 | 0,649 |
| Pulling working load kg | 1520 | 1921 | 2373 | 3400 | 4012 |
| Lifting working load wire rope kg | 912 | 1153 | 1424 | 2040 | 2407 |
| Construction | 6 x 19 | 6 x 19 | 6 x 19 | 6 x 19 | 6 x 19 |
| Wire rope Ø mm | 8 | 9 | 10 | 11,5 | 13 |

| References | CB16STG | CB18STG | CB20STG | CB22STG | CB24STG |
|-----------------------------------|---------|---------|---------|---------|---------|
| Mini. breaking load kg | 18258 | 23052 | 28458 | 34476 | 41004 |
| Theoretical weight kg/m | 0,983 | 1,240 | 1,540 | 1,860 | 2,210 |
| Pulling working load kg | 6086 | 7684 | 9486 | 11492 | 13668 |
| Lifting working load wire rope kg | 3652 | 4610 | 5692 | 6895 | 8201 |
| Construction | 6 x 19 | 6 x 36 | 6 x 36 | 6 x 36 | 6 x 36 |
| Wire rope Ø mm | 16 | 18 | 20 | 22 | 24 |

| References | CB26STG | CB28STG | CB32STG |
|-----------------------------------|---------|---------|---------|
| Mini. breaking load kg | 48144 | 55794 | 79230 |
| Theoretical weight kg/m | 2,600 | 3,010 | 3,930 |
| Pulling working load kg | 16048 | 18598 | 24310 |
| Lifting working load wire rope kg | 9629 | 11159 | 14586 |
| Construction | 6 x 36 | 6 x 36 | 6 x 36 |
| Wire rope Ø mm | 26 | 28 | 32 |



HUCHEZ
4, rue Michel HAMMID
60420 FERRIERES – France
☎ +33 (0) 3 44 51 11 33
🌐 www.huchez.com
✉ contact@huchez.fr



SERVICE CLIENTS
ATENCIO AL CLIENTE
KUNDENSERVICE

Pour en savoir plus, n'hésitez pas à nous contacter!
To know more, please contact us!
Para más información, póngase en contacto con nosotros!
Für weitere Informationen können Sie sich gerne an uns wenden!