

Galvanised non rotating wire rope 1960 N/mm², Ø 12 mm, m/l



Use:

- Used for lifting non guided loads.

Technical properties

- Metallic central core 1960 N/mm² - Right hand lay.
- High breaking load.
- Great flexibility.
- Available option: sleeved thimble loop.
- Single swivel hook recommended.

Technical characteristics of Galvanised non rotating wire rope 1960 N/mm², Ø 12 mm, m/l

| References | CB115C |
|-----------------------------------|--------|
| Mini. breaking load kg | 10800 |
| Theoretical weight kg/m | 0,560 |
| Pulling working load kg | 3600 |
| Lifting working load wire rope kg | 2160 |
| Construction | 24 x 7 |
| Wire rope Ø mm | 12 |

Technical characteristics of the other models of the range

| References | CB3C | CB5G | CB7G | CB9G | |
|-----------------------------------|--------|--------|--------|--------|------------|
| Mini. breaking load kg | 600 | 2300 | 3250 | 6600 | On request |
| Theoretical weight kg/m | 0,036 | 0,111 | 0,185 | 0,328 | On request |
| Pulling working load kg | 200 | 767 | 1250 | 2200 | On request |
| Lifting working load wire rope kg | 120 | 460 | 750 | 1320 | On request |
| Construction | 18 x 7 | 18 x 7 | 18 x 7 | 18 x 7 | On request |
| Wire rope Ø mm | 3 | 5 | 7 | 9 | >9 |

| References | CB4C | CB5C | CB7C | CB8C | CB9C |
|-----------------------------------|--------|--------|--------|--------|--------|
| Mini. breaking load kg | 1049 | 1815 | 3213 | 5510 | 6960 |
| Theoretical weight kg/m | 0,064 | 0,940 | 0,197 | 0,280 | 0,356 |
| Pulling working load kg | 350 | 605 | 1071 | 1837 | 2320 |
| Lifting working load wire rope kg | 210 | 363 | 643 | 1102 | 1392 |
| Construction | 18 x 7 | 19 x 7 | 18 x 7 | 24 x 7 | 24 x 7 |
| Wire rope Ø mm | 4 | 5 | 7 | 8 | 9 |

| References | CB10C | CB115C | CB13C | CB14C | CB158C |
|-----------------------------------|--------|---------------|--------|--------|--------|
| Mini. breaking load kg | 8820 | 10800 | 14900 | 17400 | 16785 |
| Theoretical weight kg/m | 0,464 | 0,560 | 0,779 | 0,907 | 1,030 |
| Pulling working load kg | 2940 | 3600 | 4967 | 5800 | 5595 |
| Lifting working load wire rope kg | 1764 | 2160 | 2980 | 3480 | 3357 |
| Construction | 24 x 7 | 24 x 7 | 24 x 7 | 24 x 7 | 18 x 7 |
| Wire rope Ø mm | 10 | 12 | 13 | 14 | 15,8 |

| References | CB18C | CB20C | CB22C | CB24C | CB26C |
|-----------------------------------|--------|--------|---------|---------|--------|
| Mini. breaking load kg | 29400 | 35400 | 43300 | 52600 | 48600 |
| Theoretical weight kg/m | 1,508 | 1,883 | 2,284 | 2,751 | 2,710 |
| Pulling working load kg | 9800 | 11800 | 14433 | 17533 | 16200 |
| Lifting working load wire rope kg | 5880 | 7080 | 8660 | 10520 | 9720 |
| Construction | 24 x 7 | 24 x 7 | 24 x 17 | 24 x 17 | 18 x 7 |
| Wire rope Ø mm | 18 | 20 | 22 | 24 | 26 |

| References | CB28C | CB30C | | CB3 | CB4 |
|-----------------------------------|-------|---------|------------|--------|--------|
| Mini. breaking load kg | | 80800 | On request | 800 | 1100 |
| Theoretical weight kg/m | | 4,243 | On request | 0,037 | 0,083 |
| Pulling working load kg | | 26933 | On request | 267 | 367 |
| Lifting working load wire rope kg | | 16160 | On request | 160 | 220 |
| Construction | | 24 x 17 | On request | 18 x 7 | 18 x 7 |
| Wire rope Ø mm | 28 | 30 | >30 | 3 | 4 |

| References | CB5 | CB6 | CB7 | CB8 | CB9 |
|-----------------------------------|--------|--------|--------|--------|--------|
| Mini. breaking load kg | 2300 | 3050 | 3750 | 5600 | 6600 |
| Theoretical weight kg/m | 0,111 | 0,150 | 0,185 | 0,290 | 0,328 |
| Pulling working load kg | 767 | 1017 | 1250 | 1867 | 2200 |
| Lifting working load wire rope kg | 460 | 610 | 750 | 1120 | 1320 |
| Construction | 18 x 7 | 18 x 7 | 18 x 7 | 18 x 7 | 18 x 7 |
| Wire rope Ø mm | 5 | 6 | 7 | 8 | 9 |

| References | CB115 | |
|-----------------------------------|--------|------------|
| Mini. breaking load kg | 11000 | On request |
| Theoretical weight kg/m | 0,588 | On request |
| Pulling working load kg | 3667 | On request |
| Lifting working load wire rope kg | 2200 | On request |
| Construction | 18 x 7 | On request |
| Wire rope Ø mm | 11,5 | >11,5 |



HUCHEZ
 4, rue Michel HAMMID
 60420 FERRIERES – France
 ☎ +33 (0) 3 44 51 11 33
 🌐 www.huchez.com
 ✉ contact@huchez.fr



SERVICE CLIENTS
 ATENCIO AL CLIENTE
 KUNDENSERVICE

Pour en savoir plus, n'hésitez pas à nous contacter!
 To know more, please contact us!
 Para más información, póngase en contacto con nosotros!
 Für weitere Informationen können Sie sich gerne an uns wenden!