

## Stainless steel rope, Ø 4 mm, m/l



### Use:

- Used by the sea or outdoors with specific customary requirements.

### Technical properties

- Metallic central core - Right hand lay.
- Available option: sleeved thimble loop.
- Stainless steel single eye hook recommended.

### Technical characteristics of Stainless steel rope, Ø 4 mm, m/l

References	CB4INOX
Mini. breaking load kg	830
Theoretical weight kg/m	0,061
Pulling working load kg	277
Lifting working load wire rope kg	166
Construction	7 x 19
Wire rope Ø mm	4

## Technical characteristics of the other models of the range

References	CB2_5INOX	CB3INOX	CB4INOX	CB5INOX	CB6INOX
Mini. breaking load kg	340	460	<b>830</b>	1300	1880
Theoretical weight kg/m	0,024	0,034	<b>0,061</b>	0,095	0,138
Pulling working load kg	113	153	<b>277</b>	433	627
Lifting working load wire rope kg	68	92	<b>166</b>	260	376
Construction	7 x 19	7 x 19	<b>7 x 19</b>	7 x 19	7 x 19
Wire rope Ø mm	2,5	3	<b>4</b>	5	6

References	CB7INOX	CB8INOX	CB9INOX	CB10INOX	CB12INOX
Mini. breaking load kg	2560	3330	4220	5210	7500
Theoretical weight kg/m	0,187	0,243	0,308	0,381	0,548
Pulling working load kg	853	1110	1407	1737	2500
Lifting working load wire rope kg	512	666	844	1042	1500
Construction	7 x 19	7 x 19	7 x 19	7 x 19	7 x 19
Wire rope Ø mm	7	8	9	10	11,5

References	CB14INOX	CB16INOX	CB18INOX	
Mini. breaking load kg	10200		18414	On request
Theoretical weight kg/m	0,746		1,230	On request
Pulling working load kg	3400		6138	On request
Lifting working load wire rope kg	2040		3683	On request
Construction	7 x 19		7 x 19	On request
Wire rope Ø mm	14	16	18	>18



HUCHEZ  
4, rue Michel HAMMID  
60420 FERRIERES – France  
☎ +33 (0) 3 44 51 11 33  
🌐 [www.huchez.com](http://www.huchez.com)  
✉ [contact@huchez.fr](mailto:contact@huchez.fr)



SERVICE CLIENTS  
ATENCIO AL CLIENTE  
KUNDENSERVICE

Pour en savoir plus, n'hésitez pas à nous contacter!  
To know more, please contact us!  
Para más información, póngase en contacto con nosotros!  
Für weitere Informationen können Sie sich gerne an uns wenden!