Motorised lifting equipment for sport and cultural facilities

Designed according to the Directive Machines 2006/42/EC and the norm NF EN 14492-2.

CE

YOUR CONTACT: Sales team ① : +33 (0) 344 511 133 - ⊠ : contact@huchez.fr



huchez.com



TECHNICAL CHARACTERISTICS





> 3 push buttons pendant control (Up – Down – Emergency stop).

- Plug and play. \triangleright
- Wall mounted.
- Key locking.
- 20 m pendant control.



- Articulated diverting pulley with support plate (ref. PA).
- ▶ For 5 mm Ø wire rope.
- Locking device to avoid the wire rope to go out \triangleright of the sheave groove.



Complete wire rope kit with timble loop and hook.

- Galvanised wire rope 5 mm \emptyset Metallic central ⊳ core 2170 N/mm² - Right hand or left hand lay according to the model.
- ▶ Wire rope length: 10, 15, 20 or 35 m.
- ▷ Single swivel hook.




► AGON 300 kg electric winch.

- Compact (RAL grey 7031). >
- Grooved drum.
- Good wire rope winding with the rope press role device.
- « Clock » limit switch device easy to set. >
- Very low voltage pendant control (24 V) for a > high protection against the electric risk of the operator.

| Reference | AGON 300 kg |
|----------------------|-------------|
| Capacity kg | 300 |
| Max. drum capacity m | 16 |
| Speed m/min | 5.9 |
| FEM | 1Dm |
| Power | 1Ph-230V |



Fixed diverting pulley with support plate (ref. PF). ▶ For 5 mm Ø wire rope.



- ▷ Safety device to automatically stop the fall of a load.
- ▶ Yearly visual inspection. Maintenance by the manufacturer after activation.
- ▶ Wire rope length: 10 m.
- ▶ Integrated energy absorber reducing the stress on the reception structure.

QUOTE ON REQUEST.

Sales team ① : +33 (0) 344 511 133 - ⊠ : contact@huchez.fr



huchez.com

Tel. : +33 (0) 344 511 133 contact@huchez.fr